



Zahrat Ajman Co.

P400 - P440(S)

Ratings @ 0.8 PF		Prime Rating	Stand-by Rating
Voltage*1	Frequency*2	P 400*3	P 440*4
230/400 V	50 Hz	400 KVA	440 KVA
277/480v	60Hz	410 KVA	450 KVA

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1

Gensets Medium range



Technical

Engine model	Perkins 2206A-E13TAG3	
Cylinders	6 - vertical in-line	
Aspiration	Turbocharged & A/A charge cooled	
Combustion	Direct injection	
Cooling System	Water cooled	
Displacement	12.5 liters	
Oil consumption	0.1 % of fuel consumption	
Lube oil capacity	40 liters	
Coolant capacity	51.4 liters	
Governor	Electronic	
Speed	1500 rpm	1800 rpm
Fuel Consumption @ 100% Load	81 L/H	81 L/H
Fuel Consumption @ 75% Load	62 L/H	62 L/H
Fuel Consumption @ 50% Load	42 L/H	43 L/H
Radiator Cooling Air Flow	654 m3/min	788 m3/min
Max exhaust gas flow	64.8 m3/min	73.5 m3/min
Emissions regulations	For unregulated territories	

Dimensions

Length	3420 mm
Width	1120 mm
Height	1940 mm
Weight	3080 Kg

The above performance data are valid as per the following specs:

- Diesel Fuel is according to BS2869 Class A2 or equivalent.
- Lubricating oil is according to API CI4 (15W/40).
- The coolant should be 50% antifreeze and 50% distilled water.

Alternator model	Leroy Somer LSA 47.2 S4	
Regulation	$\pm 0.5\%$	
International protection	IP23	
Insulation class	H	
Terminals	12	
Frequency	50 Hz	60 Hz
Coolant Air flow	0.9 m3/s	1.1 m3/s



Image shown may not reflect actual package

www.zahra-grp.com

Info@zahra-grp.com

+964 790 184 8067

+964 771 399 6633



Iraq Baghdad

Muaskar Al Rasheed St.